MI-WAVE®
Millimeter Wave Products Inc.

# 521D-30/387P

**TEST DATA SHEET**

## Description

Mi-Wave's 521 series high Power Fixed Attenuators

## Notes

S/N: NA

## Electrical Specifications

| | Minimal | Typical | Maximum |
|---|---|---|---|
| Frequency | 110 GHz | | 170 GHz |
| Attenuation @ 140 GHz | | 30 dB | |
| VSWR | | 1.20:1 | |
| Average Power Handling | | | 0.25 Watts CW |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

## Physical Specifications

| | |
|---|---|
| Input and Output Ports | WR-6 Waveguide. UG-387/U-M Flange |
| Material | Aluminum |
| Finish | Gold Plated |
| | |
| | |
| | |
| | |
| | |
| | |

Tested by: Kim Madden

Date: 2020-09-25

RoHS compliant

Millimeter Wave Products Inc. • 2007 Gandy Blvd N., Suite 1310, St. Petersburg, FL 33702
**Phone:** (727) 563-0034 • **Fax:** (727) 563-0031 • **Email:** Sales@miwv.com

REACH COMPLIANCE