

955BF-30/20/383H-P B-Band Amplifier 33GHz - 50GHz, WR-22

Output Power

Frequency	P1dB	Psat
(GHz)	(dBm)	(dBm)
33	+16.7	+20.6
34	+16.7	+20.1
35	+16.5	+20.2
36	+16.0	+19.7
37	+16.3	+19.9
38	+16.6	+19.7
39	+16.4	+19.7
40	+16.8	+19.8
41	+16.5	+19.9
42	+16.7	+19.7
43	+16.5	+19.8
44	+16.8	+19.6
45	+17.9	+20.0
46	+17.4	+19.8
47	+17.5	+19.6
48	+18.7	+19.9
49	+18.8	+20.2
50	+19.0	+19.8

Tested By: J.A.K.

Date: 12/16/2022

The material presented in this datasheet was current at the time of publication. Mi-Wave's continuing product improvement program makes it necessary to reserve the right to change our mechanical and electrical specifications without notice. If either of these parameters is critical, please contact the factory to verify that the information is current. This material consists of Mi-Wave's general capabilities information and does not contain controlled technical data as defined within the International Traffic in Arms (ITAR) Part 120.10 or Export Administration Regulations.(EAR) Part 734.7-11. D-405/05.01.18





miwv.com