

# 980 SERIES WR-19 U-BAND UPCONVERTER

for Satcom Applications



## KEY FEATURES

- RF Frequency: 47.5 to 52.5 GHz
- IF Frequency: DC to 10 GHz
- Integrated LO: Internal synthesizer
- LO Control: Configurable GUI or API commands
- Conversion Gain: 40 dB
- Output Power: Up to +40 dBm
- Digital Step Attenuator: 22 dB attenuation range
- Phase Control Resolution: 0.002°
- LO Operating Modes: CW, Sweep, and Hop modes with external trigger capability
- Integrated Filtering: Embedded RF cavity filter
- Power Requirement: Single +15 V supply

### U-Band Upconverter

High-performance U-band Upconverter covering RF input with DC to 10 GHz IF output, designed for demanding microwave and millimeter-wave applications. The unit features an integrated synthesizer-based LO that can be controlled through a GUI or API commands for easy system integration. It provides 40 dB gain, up to +40 dBm output power, and includes a 22 dB digital step attenuator for flexible level control.

Ultra-fine phase control with 0.002° resolution enables precise signal alignment. The LO supports CW, Sweep, and Hop modes, including external trigger operation for advanced test and system applications. An embedded RF cavity filter enhances spectral purity, and the module operates from a single +15 V supply.



SN: XXXXX

## Physical Properties

970 Series Frequency Upconverter

RF Interface	WR19 Waveguide
IF Interface	SMA-Female Coax Connector
Material	Aluminum Housing
Finish	Black Anodize Finish
LO	Internal (Synthesizer with API or GUI)

## Electrical Specifications @ 25° C

## Test Data

Parameters	Min	Typ	Max
RF Frequency Range	47.5 GHz		52.5 GHz
IF Frequency Range:	DC		10 GHz
Conversion Gain		40 dB	
Output Power			+40 dBm
DSA Attenuation Range			22 dB
Phase Control Resolution		0.002°	
Power Supply (Single)		+15V	

**NOTES:**

LO Operating Modes: CW, Sweep, and Hop modes with external trigger capability

Filtering: Integrated RF Cavity Filter

Tested by: N/A

Tested on: 3/4/26

The material presented in this datasheet was current at the time of publication. Mi-Wave's continuing product improvement program makes it necessary to reserve the right to change our mechanical and electrical specifications without notice. If either of these parameters is critical, please contact the factory to verify that the information is current. This material consists of Mi-Wave's general capabilities information and does not contain controlled technical data as defined within the International Traffic in Arms (ITAR) Part 120.10 or Export Administration Regulations.(EAR) Part 734.7-11. D-405/05.01.18

