


Physical Properties

- Material: 6061 T-6 Aluminum
- Dimensions: 10.395" x 7" x 4"
- Bias: DC Supply
- RF Port: 2.92mm (K)
- IF Port: SMA-F



SN: xxxx

*Picture shown is indicative only.

Electrical Specifications @ 25°C		Test Data			
Parameters	Specifications	Min.	Typ.	Max.	Unit
RF Input Frequency	14 to 16	14	-	16	GHz
IF Output Frequency	3 to 5	3	-	5	GHz
Internal LO Frequency	11	-	11	-	GHz
Conversion Gain	45 typ.	-	45	-	dB
Output P1dB	12 typ.		12		dBm
Psat	17 typ.		17		dBm
Reference Frequency	10	-	10	-	MHz
Reference Input Power	+3 to +7 typ.	+3	+5	+7	dBm
Supply Voltage ^{1,3}	+12Vdc Supply typ.		+12		Vdc

1. SN or PN may differ from actual unit. Please refer to outline on page 3 for more details.

2. Open and short-circuit loads are not recommended at the mixer output. Ensure proper 50 Ohm load before turning the mixer "ON".

Absolute Maximum Ratings	
Parameter	Ratings
Operating Temperature	-10°C to +45°C
Storage Temperature	-40°C to +100°C
Reference Input Power	+10dBm
RF Input Power (CW)	+10dBm
DC Operating Voltage	+12Vdc


*Permanent damage may occur if any of these are exceeded.

Biasing Up Procedure	
Step 1	Apply External Reference
Step 2	Apply DC Supply Voltage
Step 3	Turn ON RF input
Power Down Procedure	
Step 1	Turn OFF RF Input
Step 2	Turn OFF DC Supply Voltage
Step 3	Remove External Reference

The material presented in this datasheet was current at the time of publication. Mi-Wave's continuing product improvement program makes it necessary to reserve the right to change our mechanical and electrical specifications without notice. If either of these parameters is critical, please contact the factory to verify that the information is current. This material consists of Mi-Wave's general capabilities information and does not contain controlled technical data as defined within the International Traffic in Arms (ITAR) Part 120.10 or Export Administration Regulations.(EAR) Part 734.7-11. D-405/05.01.18



Conversion Gain (dB)




Tested By:

Date:

The material presented in this datasheet was current at the time of publication. Mi-Wave's continuing product improvement program makes it necessary to reserve the right to change our mechanical and electrical specifications without notice. If either of these parameters is critical, please contact the factory to verify that the information is current. This material consists of Mi-Wave's general capabilities information and does not contain controlled technical data as defined within the International Traffic in Arms (ITAR) Part 120.10 or Export Administration Regulations.(EAR) Part 734.7-11. D-405/05.01.18



Outline Drawing



The material presented in this datasheet was current at the time of publication. Mi-Wave's continuing product improvement program makes it necessary to reserve the right to change our mechanical and electrical specifications without notice. If either of these parameters is critical, please contact the factory to verify that the information is current. This material consists of Mi-Wave's general capabilities information and does not contain controlled technical data as defined within the International Traffic in Arms (ITAR) Part 120.10 or Export Administration Regulations.(EAR) Part 734.7-11. D-405/05.01.18

